

## MICROCRYSTALLINE WAX 5715A

### SPECIFICATION

5715A is a high quality microcrystalline Wax ideally suited for laminating application in food stuffs and general purpose packaging.

Laminates produced show excellent initial seal strength, good resistance to aging and are resistant to strike through at high ambient temperatures.

### Physical Properties

Test Methods	ASTM Method	Specification		Typical
		Minimum	Maximum	
Drop Melt Point °F (C )	D 127	165 (73.9)	177 (80.6)	171 (77.2)
Kinematic Viscosity, cSt @ 212 °F (100 °C)	D 445	13.8	17.25	16.0
Oil Content, Wt %	D 721	--	2.5	1.0
Saybolt Color	D 6045	+ 16	--	+16
Needle Penetration, dmm @ 77 °F (25°C)	D 1321	20	30	26

### FDA Status :

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in non food articles in contact with food and in 21 CFR 172.886 for use in food.

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. no warranty or guarantee express or implied is made regarding the performance or stability of any product, since the manner of use and conditions of storage and handling are beyond our control. No suggestion for product use or anything contained herein shall be construed as a recommendation for its use in infringement of any existing patent.

CONTACT: 302, MANDVI NAVJIVAN BLDG., 121/127 KAZI SAYED STREET, MASJID BUNDER, MUMBAI - 400 003. INDIA.  
TEL NO: +91-22-2344 443 \* FAX NO: +91-22-2342 1142 \* EMAIL: [info@bjint.com](mailto:info@bjint.com)