

Shell Microcrystalline Wax LMP

Shell Microcrystalline Wax LMP is a hydrogenated microwax derived from the residues of the vacuum distillation of crude oil.

Product data

Properties	Standard	Unit	Specification
Congeaing point	DIN ISO 2207	°C	62 - 66
Dropping point	DGF M-III 3	°C	typ. 67
Penetration at 25 °C	DIN 51 579	0.1 mm	typ. 30
Oil content	DIN ISO 2908	%	max. 1,0
Viscosity at 100 °C	DIN 51 562 / T1	mm ² /s	12 – 17
Color, Saybolt	DIN 51411	-	typ. +15
Color	visual	-	white/creamy yellow
Density at 100 °C	DIN 51 757	kg/m ³	typ. 795
Purity requirement BgVV	XXV. Empfehlung	-	complies
Purity requirement FDA	§ 172.886	-	complies

**We reserve the right to change the specification as a result of technical progress or for reasons related to production!
No guarantee or warranty is implied as to any particular applications of our products.**

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. no warranty or guarantee express or implied is made regarding the performance or stability of any product, since the manner of use and conditions of storage and handling are beyond our control. No suggestion for product use or anything contained herein shall be construed as a recommendation for its use in infringement of any existing patent. Mfg. reserves right to change/ alter/ modify the specification without any notice.

CONTACT: 302, MANDVI NAVJIVAN BLDG., 121/127 KAZI SAYED STREET, MASJID BUNDER, MUMBAI - 400 003. INDIA.
TEL NO: +91-22-2344 443 * FAX NO: +91-22-2342 1142 * EMAIL: info@bjint.com