

Microcrystalline Wax – W445

CHARACTERISTIC

PROPERTY	METHOD	SPECIFICATION
Melting Point	ASTM D 127	76.7 – 82.2 ° F
Color	ASTM D 156	+ 16 Min
Penetration	ASTM D 1321	13 – 17
Viscosity cst @100 ° C	ASTM D 445	14.3 – 18.0
Flash Point	ASTM D 92	530 Min
Origin	USA	
Packing	Slabs in carton 27.220 kgs	
Ash Content	Residue on Ignition <281> with a limit of 0.10% maximum residue	

Suggested Use : Candles, Chewing Gum, Cosmetics, Crayons, Dental Product, Hot Melt Adhesives, Lamination Grades, Modifying Grades, Paste upgrades, Pharmaceuticals Grades, Rust Proofing grades, Sculpture Grades, Sealant Grades.

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. no warranty or guarantee express or implied is made regarding the performance or stability of any product, since the manner of use and conditions of storage and handling are beyond our control. No suggestion for product use or anything contained herein shall be construed as a recommendation for its use in infringement of any existing patent.

CONTACT: 302, MANDVI NAVJIVAN BLDG., 121/127 KAZI SAYED STREET, MASJID BUNDER, MUMBAI - 400 003. INDIA.
TEL NO: +91-22-2344 443 * FAX NO: +91-22-2342 1142 * EMAIL: info@bjint.com